

§ 27.220

supply that is independent of the electrical system on your towing vessel; and

(2) Provides two-way voice communication and calling between the operating station and either—

(i) The engine room; or
(ii) A location immediately adjacent to an exit from the engine room.

(b) Twin-screw vessels with operating station control for both engines are not required to have an internal communication system.

(c) When the operating station control station and the engine room access are within 3 meters (10 feet) of each other and allow unobstructed visual contact between them, direct voice communication is acceptable instead of a communication system.

§ 27.220 If an existing towing vessel is 24 meters (79 feet) or longer in length, what are the requirements for fire pump, fire main, and fire hose? [Reserved]

§ 27.221 If an existing towing vessel is less than 24 meters (79 feet) in length, what are the requirements for fire pump and fire hose? [Reserved]

§ 27.225 What type of portable fire-extinguisher is required on an existing towing vessel? [Reserved]

§ 27.230 What are the requirements for a fuel shutoff on an existing towing vessel?

By October 8, 2001, you must have a remote fuel shutoff that meets § 27.340(f) installed on your vessel.

§ 27.235 Is a fire axe required on an existing towing vessel? [Reserved]

§ 27.240 What are the requirements for a muster list on an existing towing vessel? [Reserved]

§ 27.245 What are the crew-training requirements for fire emergencies on an existing towing vessel?

By January 19, 2000, you must ensure that drills, instruction and safety orientations that satisfy § 27.355 are performed on your vessel.

46 CFR Ch. I (10–1–01 Edition)

Subpart C—Fire Protection Measures for New Towing Vessels

§ 27.300 What are the requirements for a new towing vessel?

If your new towing vessel operates as described in § 27.100(a), then you must ensure that it complies with §§ 27.305 through 27.355 of this part.

§ 27.305 What are the requirements for a general alarm on a new towing vessel?

(a) You must ensure that your vessel is fitted with a general alarm system that:

(1) Has a contact maker at the operating station that can notify persons on board in the event of an emergency.

(2) Is capable of notifying persons in any accommodation, work space, and the engine room.

(3) In the engine room and any other area where background noise makes a general alarm hard to hear, has a supplemental flashing red light identified with a sign that reads:

Attention

General Alarm—When Alarm Sounds or Flashes Go to Your Station.

(4) Is tested at least once each week.

(b) You or the operator may use a PA system or other means of alerting all persons on your towing vessel instead of a general alarm, if—

(1) The PA system is capable of notifying persons in any accommodation or work space or the engine room;

(2) It is tested at least once each week;

(3) It can be activated from the operating station; and

(4) It complies with paragraph (a)(3) of this section.

§ 27.310 What are the requirements for fire detection on a new towing vessel?

A fire-detection system must be installed on your vessel to detect engine room fires. You must ensure that—

(a) Detectors, control units, and fire alarms are approved under 46 CFR subpart 161.002, or are listed by an independent testing laboratory;

(b) The system is installed, tested, and maintained per the manufacturer's design manual;